SPECIFICATIONS

Reference the specification guide below to help you select the correct solution for your needs.


| MODEL NUMBER | 2000 SERIES | 3000 SERIES | 4000 SERIES | 6000 SERIES |
|---|---------------------------------------|--|--|--|
| PRODUCT CODE | BH0420030 | BH0420031 | BH0420032 BH0420012 | BH0420033 BH0420013 |
| FUEL TYPE | ELECTRIC | ELECTRIC | ELECTRIC | ELECTRIC |
| COLOUR | BLACK | BLACK | BLACK WHITE | BLACK WHITE |
| HEAT AREA | 65FT | 100FT | 130FT | 160FT |
| RATED CURRENT ** | 240V/8.3A 208V/9.62A 277V/7.22A | 240V/12.5A 208V/14.42A 277V/10.83A | 240V/16.6A 208V/19.23A 277V/14.44A | 240V/25A 208V/28.85A 277V/21.66A |
| MINIMUM FLOOR CLEARANCE | WALL 72" | CEILING 96" | WALL 7 | 72" CEILING 96" |
| MOUNTING OPTIONS | | | | |
| CEILING MOUNT | ✓ | ✓ | ✓ | ✓ |
| CEILING RECESS KIT PRODUCT CODES | BH8180010 | BH8180011 | BH8180010 | BH8180011 |
| WALL MOUNT | ✓ | ✓ | ✓ | ✓ |
| RECESSED FLUSH MOUNT** | * 🗸 | ✓ | ✓ | ✓ |
| CEILING POLE MOUNT | ✓ | ✓ | ✓ | ✓ |
| TUBE SUSPENSION KIT (36") PRODUCT CODE | BH8180012 | | | |
| FREESTANDING | - | - | - | - |
| CONTROL OPTIONS | | | | |
| ON OFF | ✓ | ✓ | ✓ | ✓ |
| ON OFF PRODUCT CODE | BH3130010-1 | | | |
| DIMMER | ✓ | ✓ | ✓ | ✓ |
| DIMMER PRODUCT CODE | BH3130011-1 | | | |
| MASTER REMOTE * | ✓ | ✓ | ✓ | ✓ |
| | | | | |

Measurements displayed within this document are minimum requirements for installation. Bromic takes no responsibility for incorrect or non-compliant installations. All measurement in this document are displayed in inches.

DIMENSIONS


With a wide range of sizes available, find the ideal heater to suit your outdoor space.


PROFILE



CEILING RECESS

CEILING RECESS FRAME 2000W & 4000W






CEILING RECESS FRAME 3000W & 6000W

CEILING RECESS

2000W & 4000W



MINIMUM CEILING CAVITY

46"

57.5"

3000W & 6000W

^{*} Control up to six zones of heaters with unlimited heaters per zone from a single control. Works with dimming and on/off controllers. Control operates within 100ft of heaters.

^{**} Available in varying voltages: 240V, 208V and 277V

^{***} Black models only